Ohio Department of Transportation Prebid Questions

Project No. 100392 Sale Date - 6/10/2010

Question Submitted: 5/28/2010

Question Number: 1

Ref. #15 & 16: 12" Conduit & #6 CBThese items are to be installed within 5' of the railroad tracks. Excavation 5' below the tracks will be required. No mention of shoring is indicated. Will it be required or will the tracks be shut down for this operation? Also, if shoring is required, this could affect the completion date if not processed promptly.Ref. 45-46: Prestressed BeamsPrimary electric crosses over the top of the bridge. In order to remove and replace the beams, it will need to be relocated. Have arrangements been for this relocation?

See addendum 2

Question Submitted: 6/1/2010

Question Number: 2

Have arrangements been made with the railroad to close the railroad tracks adjacent to the project during installation of the bridge beams?

See addendum 2

Question Submitted: 6/1/2010

Question Number: 3

Replacement of the south east wingwall will require a portion of the existing wooden fence along the bike path ramp to be removed. If this fence is to be replaced, will it be connected to the proposed bridge railing? If so, please provide a detail for this connection. Will and item be added to remove and replace a portion of this fence?

See addendum 2

All prospective bidders, subcontractors, suppliers, materialmen and all others who have an interest in these prebid questions and answers are advised that these items are being provided for informational purposes only and are not part of the bidding documents. If a question warrants a clarification, the Department will issue an addenda addressing the request for clarification to all plan holders. If the Department believes that the bidding documents adequately address the request, the contractor will be advised accordingly.