

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	HOLE SEALED	
								GR	CS	FS	SI	CL	LL	PL	PI	WC			
6" TOPSOIL (DRILLERS DESCRIPTION) VERY STIFF, BROWN, SILTY CLAY, "AND" STONE FRAGMENTS, LITTLE SAND, DAMP	688.2	1																	
		2	11	6	16	67	SS-1	3.00	-	-	-	-	-	-	-	-	10	A-6b (V)	
		3		5															
	683.2	4	4	4	12	89	SS-2	3.00	37	9	10	21	23	38	19	19	14	A-6b (4)	
VERY STIFF, ORANGISH BROWN, CLAY, SOME STONE FRAGMENTS, TRACE SAND, MOIST		5																	
	681.2	6	5																
		7	6		-	100	SS-3A	2.50	23	5	5	31	36	44	21	23	26	A-7-6 (12)	
LIMESTONE, GRAYISH ORANGE WITH LIGHT GRAY, HIGHLY WEATHERED, WEAK TO SLIGHTLY STRONG, THICK BEDDED, FOSSILIFEROUS, VUGGY, ARENACEIOUS, CONTAINS THIN CLAY SEAMS; RQD 60%, REC 94%.		7	50/2"				SS-3B	-	-	-	-	-	-	-	-	-	-	8	Rock (V)
		8																	
		9																	
		10	39		89		NQ2-1												CORE
@ 11.3' TO 11.6'; Qu = 1,174 PSI		11																	
		12																	
		13																	
@ 14.8' TO 15.1', Qu = 2,224 PSI		14																	
		15																	
	671.6	16																	
LIMESTONE, LIGHT GRAY WITH DARK YELLOWISH BROWN, MODERATELY WEATHERED, SLIGHTLY TO MODERATELY STRONG, THICK BEDDED, FOSSILIFEROUS, VUGGY, PETROLIFEROUS; RQD 92%, REC 100%.		17	88		100		NQ2-2												CORE
@ 17.4' TO 17.7', Qu = 3,659 PSI		18																	
		19																	
		20																	
		21																	
		22																	
		23																	
		24																	
		25																	
		26																	
		27	90		100		NQ2-3												CORE
		28																	
		29																	
		30																	
		31																	
	656.2	32																	
		EOB																	

STANDARD ODOT SOIL BORING LOG (11 X 17) - OH.DOT.GDT - 7/17/14 14:09 - X:\DESIGN\CADD STANDARDS\SAMPLE PLANS\2014 EDITS\SEI\GEOTECHNICAL\GINT1100465.GPJ

NOTES: HOLE DRY BEFORE CORING. BORING PLOTTED FROM DRILLERS GPS. ELEVATION FROM DISTRICT CADD FILES.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: MIXED 25 LB. BENTONITE POWDER; 8 GAL. WATER