

PID: 87935	SFN: 4505646 (E)	PROJECT: LIC-310-0.74	STATION / OFFSET: 23+27.25 RT.	START: 8/12/14			END: 8/13/14			PG 2 OF 2	B-004-0-14				
				GR	CS	FS	SI	CL	LL			PL	WC		
MATERIAL DESCRIPTION AND NOTES			SPT/ RQD	N ₆₀	REC SAMPLE (%)	HP (tsf)	GRADATION (%)			ODOT CLASS (GI)	HOLE SEALED				
							GR	CS	FS			SI	CL	LL	PL
VERY DENSE, BROWN, SANDY SILT, TRACE CLAY, WET (continued)			8	41	44	-	-	-	-	-	-	23	A-4a (V)		
			13	14											
STIFF TO VERY STIFF, GRAY, SILT, "AND" CLAY, TRACE FINE SAND, MOIST TO WET			5	35	67	2.00	0	3	59	38	24	19	5	25	A-4b (8)
			9	14											
@ 70' TO 95', LITTLE CLAY			6	41	50	-	-	-	-	-	-	-	28	A-4b (V)	
			12	15											
			8	42	39	2.50	-	-	-	-	-	-	20	A-4b (V)	
			13	15											
			5	30	100	2.50	0	7	78	15	25	16	9	24	A-4b (8)
			7	13											
			12	54	89	1.00	-	-	-	-	-	-	25	A-4b (V)	
			16	20											
			5	54	100	2.50	-	-	-	-	-	-	22	A-4b (V)	
			17	19											
			12	48	100	2.50	-	-	-	-	-	-	22	A-4b (V)	
			16	16											
			5	36	100	4.00	0	5	58	37	22	17	5	17	A-4b (8)
			11	13											
			100												
			101												
			990.9												
			EOB												

NOTES: SAND HEAVE @ 25' (2'), 35.5' (2.6'), 40.5' (2'), 45.5' (1'), 55' (1.5'), 60' (3'), 65' (2'), AND 85' (2'). BORING LOCATIONS FROM DISTRICT SURVEY. ABANDONMENT METHODS: MATERIALS QUANTITIES: 25 LB. BENTONITE CHIPS; TREMIED 250 LB. BENTONITE POWDER; 90 GAL. WATER