



# OHIO DEPARTMENT OF TRANSPORTATION

CENTRAL OFFICE • 1980 WEST BROAD STREET • COLUMBUS, OH 43223

JOHN KASICH, GOVERNOR • JERRY WRAY, DIRECTOR

Date: July 15, 2011

To: Users of the Hydraulic Standard Construction Drawings

Re: Hydraulic Standard Construction Drawing Revisions

Transmitted herewith are revisions to the Hydraulic Standard Construction Drawings. The following significant revisions have been made.

#### DM-1.4

- The minimum depth for the initial backfill was changed from 12" to 6" for Plastic Conduit, Type C & D – Fill and also for Plastic Conduit, Type C-Cut on page 2/2. This was done to match changes in ASTM D2321.

Copies of all of the current Hydraulic Standard Construction Drawings are available in Microstation and PDF formats on our website at:

<http://www.dot.state.oh.us/Divisions/Engineering/Structures/standard/Pages/Revisions.aspx>.

Technical questions or recommended changes should be directed to Jeff Syar (614) 275-1373 or Rebecca Humphreys (614) 387-1125.

Respectfully,

A handwritten signature in black ink that reads "Jeff Syar". The signature is written in a cursive style with a large initial "J".

Jeff Syar, P.E.

Hydraulic Section Head

JS:rjh