

Office of Roadway Engineering
Type III Barricades (Category II)
 Last Updated: June 22, 2021

MASH-16

MASH-16 Compliant Type III Barricades:

NOTE: PLEASE CAREFULLY REVIEW THE RESTRICTIONS IN WHICH EACH DEVICE IS APPROVED. THERE ARE MULTIPLE DEVICES THAT MEET BOTH NCHRP-350 AND MASH COMPLIANCE, HOWEVER THEY ARE APPROVED WITH DIFFERING RESTRICTION CRITERIA. A DEVICE LISTED UNDER MASH COMPLIANCE IS ONLY APPROVED UNDER THE CONDITIONS OF WHICH ARE STATED UNDER THE MASH APPROVED LIST COLUMN FOR RESTRICTIONS AND THE APPLICABLE FHWA ELIGIBILITY LETTER(S). APPROVALS AND RESTRICTIONS LISTED UNDER NCHRP-350 FOR ANY DEVICE ARE NOT APPLICABLE TO THE MASH VERSION OF THE DEVICE UNLESS OTHERWISE SPECIFIED.

Manufacturer	Product/Model	Description	Date	Remarks
PEXCO, LLC 3110 70th Ave East Tacoma, WA, 98424 253-284-8000 Fax 253-284-8080 www.pexco.com	Type III Barricade Assembly T3B T3BX	TYPE III BARRICADE WITH 1" X 8" X 48"-144" PANELS MADE OF HDPE TREATED TO RETAIN REFLECTIVE SHEETING, THE UPRIGHTS CAN BE PSST STEEL OR X-TUBE PLASTIC, FEET CAN BE ANGLE IRON OR PSST STEEL.	8/7/2020	Approved MASH 16 Report: WZ-380 (3/26/2019), WZ-381 (3/26/2019) RESTRICTIONS - THE MOUNTING OF SIGNS OR LIGHTS OF ANY TYPE IS NOT APPROVED IN ANY CONFIGURATION.
Plastic Safety Systems Inc. 2444 Baldwin Road Cleveland, OH 44104 Phone: 1-800-662-6338 Fax: 1-216-231-2702 www.pss-innovations.com	TYPE III BARRICADE	ANCHOR MAST SYSTEM TYPE III BARRICADE CONSISTING OF THREE HORIZONTAL RETROREFLECTIVE WAVE BOARDS 4', 6', OR 8' IN LENGTH. THE BASES, UPRIGHTS, AND WAVE BOARDS ARE CONSTRUCTED OF HDPE MATERIAL. ANCHOR BASE IS 48" IN LENGTH.	8/14/2020	Approved MASH 16 Report: WZ-389 (5/4/2020) RESTRICTIONS - THE MOUNTING OF SIGNS OR LIGHTS OF ANY TYPE IS NOT APPROVED IN ANY CONFIGURATION.
Plasticade Products 7700 North Austin Avenue Skokie, IL 60077 Phone: 1-800-772-0355 Fax: 1-847-966-8074 www.plasticade.com	SENTINEL TYPE III BARRICADE	4' - 6' ALL PLASTIC TYPE III BARRICADE. BASE CONSISTS OF 2 PIECES, UPRIGHT AND BASE THAT SNAP TOGETHER. BASE CAN BE INTERNALLY BALLASTED WITH SAND. PLASTIC BOARDS ARE REFLECTORIZED WITH 3M BRAND ODOT APPROVED SHEETING.	8/7/2020	Approved MASH 16 Report: WZ-302 (3/11/2011) RESTRICTIONS - THE MOUNTING OF SIGNS OF ANY TYPE IS NOT APPROVED IN ANY CONFIGURATION.
	BREAK-AWAY TYPE III BARRICADE	4' - 12' ALL PLASTIC TYPE III BARRICADE. BARRICADE IS COLLAPSIBLE FOR TRANSPORT AND STORAGE. PLASTIC BOARDS ARE REFLECTORIZED WITH 3M BRAND ODOT APPROVED SHEETING.	8/7/2020	Approved MASH 16 Report: WZ-299 (3/10/2011) RESTRICTIONS - THE MOUNTING OF SIGNS OF ANY TYPE IS NOT APPROVED IN ANY CONFIGURATION.
TraFFix Devices, Inc. 160 Avenida La Pata San Clemente, CA 92673 Phone: 1-949-361-5663 Fax: 1-949-573-9250 info@traffixdevices.com www.traffixdevices.com	ECONOMY TYPE III BARRICADE	TYPE III BARRICADE CONSISTING OF 4', 6' OR 8' PLASTIC RAILS WITH STEEL ANGLE UPRIGHTS AND LEGS. ACCEPTABLE FOR USE WITH OR WITHOUT BALLAST SAND BAGS, A WARNING LIGHT MOUNTED TO THE UPRIGHT, AND 48" x 36" RIGID SIGN MOUNTED TO THE HORIZONTAL PLASTIC PANELS.	11/3/2020	Approved MASH 16 Report: WZ-404 (5/26/2020) TYPE III BARRICADE 48" (4FT.) WIDE TO 96" (8FT.) WIDE FOR USE AS A SIGN SUPPORT WITH A 48"x36" SINGLE RIGID SIGN CONSTRUCTED OF .080 ALUMINUM SIGN SUBSTRATE. RESTRICTIONS - THIS DEVICE IS ONLY PERMITTED FOR USE WITH RAIL WIDTHS OF 4', 6', AND 8'.

NCHRP 350 Compliant Type III Barricades:

Manufacturer	Product/Model	Description	Date	Remarks
Bent Manufacturing Company 15442 Chemical Lane Huntington Beach, CA 92649 Phone: 1-714-842-0600 Fax: 1-714-842-2959 bmc@bentmfg.com www.bentmfg.com	PORTABLE TYPE III PLYWOOD PANEL BARRICADE	4' - 8' BARRICADE WITH 1" X 8" X 48" - 96" PLYWOOD PANELS REFLECTORIZED WITH TYPE III HIGH INTENSITY REFLECTIVE SHEETING MOUNTED ON TWO 1-1/2" X 1-1/2" X 3/16" X 63" ANGLE STEEL UPRIGHTS ATTACHED TO TWO 1-1/2" X 1-1/2" X 3/16" X 60" ANGLE STEEL BASE STANDS WITH 2" X 2" X 8" SQUARE STEEL TUBING RECEIVERS	1/1/05	APPROVED NCHRP REPORT 350: WZ-6 (11/23/1998) RESTRICTIONS -- SUPPLEMENTARY SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE CONSTRUCTED WITH AN APPROVED ALUMINUM LAMINATE SUBSTRATE. THE APPROVED ALUMINUM LAMINATE SUBSTRATES SHALL BE EITHER ALPOLIC, DIBOND, OR REYNOLITE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM TO A TYPE III BARRICADE IS PROHIBITED. RESTRICT TO 25 SQ.FT.
Eastern Metal/USA 1430 Sullivan St. Elmira, NY 14901 Phone: 607-734-2295 Fax: 607-734-8783 easternmetalsignsandsafety.com	TYPE III BARRICADE BC-3000 SERIES	TYPE III BARRICADE WITH 1" x 8" x 48"-96" EXTRUDED PLASTIC RAILS REFLECTORIZED WITH 6" EG, HI or DG REFLECTIVE SHEETING, UPRIGHTS OF 14 GAUGE STEEL TELESPAR, SQUARE TUBING, 5' HIGH ATTACHED TO TWO 14 GAUGE STEEL TELESPAR, SQUARE TUBE FEET.	10/29/19	APPROVED NCHRP REPORT 350: WZ-54 (9/15/2000), WZ-55 (12/18/2000), WZ-76 (5/31/2001), and WZ-85 (11/15/2001) TYPE III BARRICADE PANEL AT 96" (8 ft.) WIDE IS NOT PERMITTED TO HAVE SIGNS MOUNTED. RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE CONSTRUCTED OF 2 MM THICK ALPOLIC 350 SIGN SUBSTRATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 25 TOTAL SQUARE FEET OF NOTED SIGN SUBSTRATE. SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE. THE TOP OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE TOP OF THE TOP RAIL, THE MINIMUM MOUNTING HEIGHT IS 12 INCHES ABOVE THE ROADWAY.
Korman Signs, Inc. 3029 Lincoln Avenue Henrico, VA 23228-4295 Phone: 1-800-296-6050 Fax: 1-804-261-1040 www.kormansigns.com	WBT3 TYPE III BARRICADE	PORTABLE TYPE III BARRICADE UTILIZING 1 3/4" OR 2" PSST SQUARE TUBING UPRIGHTS, LEGS AND OPTIONAL CROSSBAR BOLTED TOGETHER USING SPLICE PLATES	7/10/03	APPROVED NCHRP REPORT 350: WZ-100#3 (7/10/2003) RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO KORMAN SIGNS TYPE III BARRICADES SHALL BE CONSTRUCTED WITH 2MM ALPOLIC 350, REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT ALUMINUM COMPOSITE LAMINATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 33 TOTAL SQUARE FEET OF 2MM ALPOLIC 350, REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE WITH A MINIMUM OF 12" TO THE GROUND. THE BOTTOMS OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE BOTTOM OF THE TOP RAIL.
Korman Signs, Inc. 3029 Lincoln Avenue Henrico, VA 23228-4295 Phone: 1-800-296-6050 Fax: 1-804-261-1040 www.kormansigns.com	"WBT3-SW" 5'-7' TALL TYPE III HOLLOW PLASTIC OR 2MM ALPOLIC PANEL BARRICADE	4' - 12' BARRICADE WITH EITHER HOLLOW EXTRUDED PLASTIC OR 2MM ALPOLIC PANELS REFLECTORIZED WITH ANY 3M BRAND, ODOT APPROVED BARRICADE SHEETING MOUNTED ON TWO 1 3/4" X 1 3/4" X 60" OR 84" 14 GAUGE GALVANIZED PERFORATED SQUARE STEEL TUBING UPRIGHTS ATTACHED TO TWO 1 3/4" X 1 3/4" X 60" 14 GAUGE GALVANIZED PERFORATED SQUARE STEEL TUBING BASE LEGS BY WELDED STUBS THAT FIT INSIDE THE UPRIGHTS WITH NO HORIZONTAL CROSS BRACE.	1/1/05	APPROVED NCHRP REPORT 350: WZ-100 (6/20/2002), WZ-100#3 (7/10/2003) and WZ-100#6 (3/4/2005). RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO KORMAN SIGNS TYPE III BARRICADES SHALL BE CONSTRUCTED WITH 2MM ALPOLIC 350 REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT ALUMINUM COMPOSITE LAMINATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 33 TOTAL SQUARE FEET OF 2MM ALPOLIC 350, REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE WITH A MINIMUM OF 12" TO THE GROUND. THE BOTTOMS OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE BOTTOM OF THE TOP RAIL.
Korman Signs, Inc. 3029 Lincoln Avenue Henrico, VA 23228-4295 Phone: 1-800-296-6050 Fax: 1-804-261-1040 www.kormansigns.com	"WBT3-SWH" 5'-7' TALL TYPE III HOLLOW PLASTIC OR 2MM ALPOLIC PANEL BARRICADE	4' - 12' BARRICADE WITH EITHER HOLLOW EXTRUDED PLASTIC OR 2MM ALPOLIC PANELS REFLECTORIZED WITH ANY 3M BRAND, ODOT APPROVED BARRICADE SHEETING MOUNTED ON TWO 1 3/4" X 1 3/4" X 60" OR 84" 14 GAUGE GALVANIZED PERFORATED SQUARE STEEL TUBING UPRIGHTS ATTACHED TO TWO 1 3/4" X 1 3/4" X 60" 14 GAUGE GALVANIZED PERFORATED SQUARE STEEL TUBING BASE LEGS BY WELDED STUBS THAT FIT INSIDE THE UPRIGHTS WITH HORIZONTAL CROSS BRACE.	1/1/05	APPROVED NCHRP REPORT 350: WZ-100 (6/20/2002), WZ-100#3 (7/10/2003) and WZ-100#6 (3/4/2005). RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO KORMAN SIGNS TYPE III BARRICADES SHALL BE CONSTRUCTED WITH 2MM ALPOLIC 350 REYNOL; TE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT ALUMINUM COMPOSITE LAMINATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 33 TOTAL SQUARE FEET OF 2MM ALPOLIC 350, REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE WITH A MINIMUM OF 12" TO THE GROUND. THE BOTTOMS OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE BOTTOM OF THE TOP RAIL.

<p>Korman Signs, Inc. 3029 Lincoln Avenue Henrico, VA 23228-4295 Phone: 1-800-296-6050 Fax: 1-804-261-1040 www.kormansigns.com</p>	<p>“EZ-KADE, WBT3-HP” TYPE III HOLLOW PLASTIC OR 2MM ALPOLIC PANEL BARRICADE</p>	<p>4' - 12' BARRICADE WITH EITHER HOLLOW EXTRUDED PLASTIC OR 2MM ALPOLIC PANELS REFLECTORIZED WITH ANY 3M BRAND, ODOT APPROVED BARRICADE SHEETING MOUNTED ON TWO 1 3/4" X 1 3/4" X 60" OR 84" 14 GAUGE GALVANIZED PERFORATED SQUARE STEEL TUBING UPRIGHTS ATTACHED TO TWO 1 3/4" X 1 3/4" X 60" 14 GAUGE GALVANIZED PERFORATED SQUARE STEEL TUBING BASE LEGS BY HINGE PLATE BRACKETS WITH NO HORIZONTAL CROSS BRACE.</p>	<p>1/1/05</p>	<p>APPROVED NCHRP REPORT 350: WZ-100 (6/20/2002), WZ-100#3 (7/10/2003), WZ-100#4 (1/7/2004) and WZ-100#6 (3/4/2005).</p> <p>RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO KORMAN SIGNS TYPE III BARRICADES SHALL BE CONSTRUCTED WITH 2MM ALPOLIC 350, REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT ALUMINUM COMPOSITE LAMINATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 33 TOTAL SQUARE FEET OF 2MM ALPOLIC 350, REYNOLITE, DIBOND OR OTHER FHWA APPROVED EQUIVALENT SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE WITH A MINIMUM OF 12" TO THE GROUND. THE BOTTOMS OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE BOTTOM OF THE TOP RAIL.</p>
<p>PEXCO, LLC 3110 70th Ave East Tacoma, WA, 98424 253-284-8000 Fax 253-284-8080</p>	<p>Type III Barricade Assembly</p>	<p>Assembly of the upright, feet and poly boards using reflective tape of desired intensity. Intended to be used to close roads or access to roadways temporarily. All plastic construction except for the feet of the barricade. Fully crash tested.</p>	<p>1/7/10</p>	<p>APPROVED NCHRP 350: HAS-1/WZ-39 (6/29/2000)</p>
<p>Plastic Safety Systems Inc. 2444 Baldwin Road Cleveland, OH 44104 Phone: 1-800-662-6338 Fax: 1-216-231-2702 www.plasticsafety.com</p>	<p>TYPE III BARRICADE MODEL# T3-A SERIES</p>	<p>ANCHOR SYSTEM TYPE III WITH MAST SYSTEM WITH 12' AND SMALLER RAILS WITH UP TO 25 SQUARE FEET OF LIGHTWEIGHT SUBSTRATE SIGNS MOUNTED ON OR ABOVE THE TOP RAIL WITH A MINIMUM HEIGHT TO THE TOP OF 87" WITH OR WITHOUT LIGHTS</p>	<p>1/1/05</p>	<p>APPROVED NCHRP 350: WZ-152 (4/10/2003), WZ-166 (11/12/2003), and WZ-196 (2/25/2005)</p> <p>RESTRICTIONS - SIGNS MADE OF ALUMINUM ARE NOT APPROVED TO BE MOUNTED IN ANY CONFIGURATION.</p>
<p>Plasticade Products 7700 North Austin Avenue Skokie, IL 60077 Phone: 1-800-772-0355 Fax: 1-847-966-8074 www.plasticade.com</p>	<p>SENTINEL TYPE III BARRICADE</p>	<p>4'- 6' ALL PLASTIC TYPE III BARRICADE. BASE CONSISTS OF 2 PIECES, UPRIGHT AND BASE THAT SNAP TOGETHER. BASE CAN BE INTERNALLY BALLASTED WITH SAND. PLASTIC BOARDS ARE REFLECTORIZED WITH 3M BRAND ODOT APPROVED SHEETING.</p>	<p>6/5/09</p>	<p>APPROVED NCHRP REPORT 350: WZ-104 (1/11/2002)</p>
<p>Plasticade Products 7700 North Austin Avenue Skokie, IL 60077 Phone: 1-800-772-0355 Fax: 1-847-966-8074 www.plasticade.com</p>	<p>PLASTICADE BREAK-AWAY TYPE III BARRICADE</p>	<p>4' - 12' ALL PLASTIC TYPE III BARRICADE. BARRICADE IS COLLAPSIBLE FOR TRANSPORT AND STORAGE. PLASTIC BOARDS ARE REFLECTORIZED WITH 3M BRAND ODOT APPROVED SHEETING.</p>	<p>6/5/09</p>	<p>APPROVED NCHRP REPORT 350: WZ-89 (2/7/2002)</p>
<p>Protection Services Inc. 635 Lucknow Road Harrisburg, PA 17110 Phone: 1-866-489-1234 Fax: 1-717-236-1281 www.protectionservices.com</p>	<p>TYPE III BARRICADE WITH WOOD, PLYWOOD, PLASTIC OR PLASTIC HOLLOW CORE STRIPED PANELS</p>	<p>TYPE III BARRICADE WITH 1/2" X 8" X 48" - 96" PANELS REFLECTORIZED WITH TYPE "G" HIGH INTENSITY REFLECTIVE SHEETING MOUNTED ON TWO 1-1/2" X 1-1/2" X 3/16" X 63" - 72" PERFORATED SQUARE STEEL TUBING (PSST) UPRIGHTS ATTACHED TO TWO 1-3/4" X 1-3/4" X 3/16" X 60" ANGLE STEEL OR SQUARE TUBE STEEL BASE STANDS WITH 1-3/4" X 1-3/4" X 18" SQUARE STEEL TUBING OR PSST RECEIVERS</p>	<p>1/1/05</p>	<p>APPROVED NCHRP REPORT 350: WZ-70 (3/7/2001) WITH REFERENCE TO: WZ-40 (6/6/2000), WZ-44 (7/25/2000), WZ-54 (9/15/2000), & WZ-55 (12/18/2000).</p> <p>TYPE III BARRICADE FROM 48" (4 ft.) TO 96" (8 ft.) WIDE WITHOUT SIGNS.</p> <p>TYPE III BARRICADE 48" (4 ft.) WIDE TO 72" (6ft.) WIDE FOR USE AS A SIGN SUPPORT WITH SINGLE OR MULTIPLE RIGID SIGNS CONSTRUCTED OF WOOD, PLYWOOD, OR .080 ALUMINUM SIGN SUBSTRATE.</p> <p>RESTRICTIONS -- SUPPLEMENTARY RIGID SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE LIMITED TO A MASS OF 25 lbs. EACH OR LESS, OR BE CONSTRUCTED OF AN APPROVED LIGHTWEIGHT SIGN SUBSTRATE. EITHER SINGLE OR MULTIPLE SIGNS UP TO 25 TOTAL SQUARE FEET, ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE WITH A MINIMUM OF 12" TO THE GROUND. ONE SIGN UP TO MAXIMUM 48X48 INCHES MAY BE MOUNTED ABOVE THE TOP OF THE TOP RAIL. FLASHING LIGHTS, IF USED, SHALL WEIGH A MAXIMUM OF 3.3 lbs. AND BE MOUNTED TO THE TOP OF THE PSST TYPE III BARRICADE/SIGN SUPPORT UPRIGHTS.</p>

Three D Traffic Works 430 N. Varney Street Burbank, CA 91502 Phone (Toll Free): 1-877-843-9757 Phone: 1-818-954-8453 Fax: 1-818-841-5096 sales@trafficwks.com www.trafficwks.com	TD2500 (WOOD & ANGLE STEEL)	CARBON STEEL UPRIGHT FRAME AND BASE STAND WITH 2"X2" SQUARE TUBING RECEIVER.	1/1/05	APPROVED NCHRP REPORT 350: WZ-54 (9/15/2000), WZ-85 (11/15/2001) RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE CONSTRUCTED OF 2 MM THICK ALPOLIC 350 SIGN SUBSTRATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 25 TOTAL SQUARE FEET OF NOTED SIGN SUBSTRATE. SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE. THE TOP OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE TOP OF THE TOP RAIL, THE MINIMUM MOUNTING HEIGHT IS 12 INCHES ABOVE THE ROADWAY.
Three D Traffic Works 430 N. Varney Street Burbank, CA 91502 Phone (Toll Free): 1-877-843-9757 Phone: 1-818-954-8453 Fax: 1-818-841-5096 sales@trafficwks.com www.trafficwks.com	TD2550 (WOOD & PSST)	CAN ACCOMMODATE FLASHING LIGHTS. FRAME MADE WITH UNISTRUT'S TELEPAR TUBING WITH BREAKAWAY BASE, BRACKET AND DETACHABLE FEET.	1/1/05	APPROVED NCHRP REPORT 350: WZ-54 (9/15/2000), WZ-85 (11/15/2001) RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE CONSTRUCTED OF 2 MM THICK ALPOLIC 350 SIGN SUBSTRATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 25 TOTAL SQUARE FEET OF NOTED SIGN SUBSTRATE. SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE. THE TOP OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE TOP OF THE TOP RAIL, THE MINIMUM MOUNTING HEIGHT IS 12 INCHES ABOVE THE ROADWAY.
Three D Traffic Works 430 N. Varney Street Burbank, CA 91502 Phone (Toll Free): 1-877-843-9757 Phone: 1-818-954-8453 Fax: 1-818-841-5096 sales@trafficwks.com www.trafficwks.com	TD2600 (PLASTIC RAIL & ANGLE STEEL)	CARBON STEEL UPRIGHT FRAME AND BASE STAND WITH 2"X2" SQUARE TUBING RECEIVER.	1/1/05	APPROVED NCHRP REPORT 350: WZ-128 (7/12/2002) RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE CONSTRUCTED OF 2 MM THICK ALPOLIC 350 SIGN SUBSTRATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 25 TOTAL SQUARE FEET OF NOTED SIGN SUBSTRATE. SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE. THE TOP OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE TOP OF THE TOP RAIL, THE MINIMUM MOUNTING HEIGHT IS 12 INCHES ABOVE THE ROADWAY.
Three D Traffic Works 430 N. Varney Street Burbank, CA 91502 Phone (Toll Free): 1-877-843-9757 Phone: 1-818-954-8453 Fax: 1-818-841-5096 sales@trafficwks.com www.trafficwks.com	TD2650 (PLASTIC & PSST)	CAN ACCOMMODATE FLASHING LIGHTS.FRAME MADE WITH UNISTRUT'S TELEPAR TUBING WITH BREAKAWAY BASE, BRACKET AND DETACHABLE FEET.	1/1/05	APPROVED NCHRP REPORT 350: WZ-128 (7/12/2002) RESTRICTIONS -SUPPLEMENTARY SIGNS ATTACHED TO TYPE III BARRICADES SHALL BE CONSTRUCTED OF 2 MM THICK ALPOLIC 350 SIGN SUBSTRATE. ATTACHING ANY OTHER TYPE OF RIGID SIGN SUBSTRATUM IS PROHIBITED. UP TO 25 TOTAL SQUARE FEET OF NOTED SIGN SUBSTRATE. SINGLE OR MULTIPLE SIGNS MAY BE ATTACHED DIRECTLY TO THE RAILS ANYWHERE ON THE BARRICADE. THE TOP OF RECTANGULAR SIGNS MAY BE AS HIGH AS THE TOP OF THE TOP RAIL, THE MINIMUM MOUNTING HEIGHT IS 12 INCHES ABOVE THE ROADWAY.
TraFFix Devices, Inc. 160 Avenida La Pata San Clemente, CA 92673 Phone: 1-949-361-5663 Fax: 1-949-573-9250 info@traffixdevices.com www.traffixdevices.com	TYPE III BARRICADE MODEL# 50000 SERIES (As of 2017 no longer being manufactured)	BREAKAWAY TYPE III WITH PLASTIC UPRIGHTS/RAILS WITH 48" X 48" SIGN AND IS ONLY "ACCEPTABLE WITH A LIGHTWEIGHT PLASTIC SIGN" SUBSTRATE.	1/1/05	APPROVED NCHRP REPORT 350: WZ-108 (2/8/2002)

Contact Person: Christopher Wilson, Office of Roadway Engineering
614-387-4232; Christopher.Wilson@dot.ohio.gov