

Ohio Department of Transportation - Prebid Questions

Project No. 110596

Sale Date - 12/1/2011

ASD-82771 - US-224-0.00, PART 1;ASD-224-7.58, PART 2

Question Submitted: 11/22/2011 12:00:07 PM

On sheets 36, 39, and 42, the plans state that 'no traffic shall be allowed on the intermediate course on the bridge.' This will require the contractor to place the surface course on the bridge before the mainline is paved. This work is inefficient and adds joints in the surface course. These added joints will affect the long term ride and maintenance of the pavement. Will ODOT consider allowing traffic on the intermediate course?

We understand this is not preferred. However, due to the thin layer of intermediate course on the bridge deck, we need to protect the Type 3 waterproofing from the traffic.

Question Submitted: 11/22/2011 11:02:11 AM

District 3 typically includes an as per plan note for 9.5mm asphalt mixes, modifying the requirements from those in the spec book. This note was not included in these plans. Was this an oversight or on this project does the district want to follow the spec as written?

Please follow the plan specifications.

Question Submitted: 11/21/2011 3:53:49 PM

Bid Ref # 67 calls for High Strength Grout for Shear key repair. On the APPROVED PRODUCTS list it states "there are no products approved at this time" for high strength grout for shear keys.

In the Proposal, Proposal Note 527 addresses the type of grout to be used for the shear key repair.

PN 527 - 04/15/2005 - ITEM 515 - HIGH EARLY STRENGTH KEYWAY GROUT FOR PRESTRESSED/POST-TENSIONED CONCRETE MEMBERS