

**NOTES**

**APPLICATION:** Provide Full Height Headwalls for skewed and non-skewed culverts having a diameter or rise of 42" to 84" inclusive. Use Type "A" when the skew angle ( $\phi$ ) is ten degrees or less and Type "B" when the skew angle is over ten degrees.

**CONCRETE:** Use 4000 psi compressive strength concrete.









**REINFORCING STEEL:** Provide epoxy coated #5 bars.


**DETAILS AND QUANTITIES:** Are shown for circular sections only. When used with reinforced elliptical concrete pipe or corrugated metal pipe arches, adjust dimensions and quantities to conform to those listed for the nearest size circular pipe. Apply the dimensions established by vertical diameter to span. Round all calculated dimensions established by horizontal diameter to the nearest 1". Chamfer all exposed corners  $\frac{3}{4}$ ".

**FOUNDATION:** Where the soil borings indicate a bearing capacity of less than 2,600 pounds per square foot, increase the width of the footing.


**HEADWALL LOCATION:** Determine by the intersection of the embankment slope at the back of the headwall at point "K". Provide 2:1 slopes adjacent to the headwall.

**PAYMENT:** Item 602 Concrete Masonry includes reinforcing.






RIGID PIPE



CORRUGATED PIPE  
END TREATMENT OF HEADWALL



LOCATION AND GRADING PLAN FOR  
SKEWED PIPE CULVERT - TYPE B

FULL-HEIGHT HEADWALLS (English)

PIPE DIA. D	H	a	b	c	Bar# d	$\phi \approx 0^\circ$					$\phi \approx 15^\circ$					$\phi \approx 30^\circ$					$\phi \approx 45^\circ$					PIPE DIA. D						
						L <sub>2</sub>	h <sub>2</sub>	Conc. CMP (cy)	Conc. RCP (cy)	Steel (lbs.)	L <sub>1</sub>	L <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	Conc. CMP (cy)	Conc. RCP (cy)	Steel (lbs.)	L <sub>1</sub>	L <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	Conc. CMP (cy)	Conc. RCP (cy)	Steel (lbs.)	L <sub>1</sub>		L <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	Conc. CMP (cy)	Conc. RCP (cy)	Steel (lbs.)
42"	4'-11"	3'-3"	1'-6"	2'-6"	#5	3'-7"	3'-1"	7.0	6.7	598	8'-9"	4'-6"	3'-8"	3'-2"	7.3	7.1	619	7'-10"	5'-9"	3'-2"	3'-3"	7.5	7.3	633	7'-10"	7'-9"	3'-2"	3'-3"	8.7	8.5	718	42"
48"	5'-5"	3'-6"	1'-6"	2'-9"	#5	4'-4"	3'-4"	8.5	8.2	793	10'-0"	5'-4"	4'-1"	3'-5"	9.0	8.7	776	8'-9"	6'-10"	3'-5"	3'-6"	9.1	8.8	801	8'-9"	9'-2"	3'-5"	3'-7"	10.6	10.3	925	48"
54"	5'-11"	3'-9"	1'-6"	3'-0"	#5	5'-2"	3'-8"	10.3	10.0	1,069	11'-4"	6'-3"	4'-6"	3'-8"	10.9	10.5	1,026	9'-8"	7'-11"	3'-8"	3'-9"	10.8	10.5	1,024	9'-8"	10'-7"	3'-8"	3'-10"	12.6	12.2	1,188	54"
60"	6'-6"	4'-0"	1'-6"	3'-3"	#5	5'-11"	3'-11"	12.3	11.8	1,149	12'-7"	7'-2"	4'-10"	4'-0"	12.9	12.4	1,174	10'-7"	9'-0"	3'-10"	4'-1"	12.7	12.3	1,157	10'-7"	12'-0"	3'-10"	4'-1"	14.8	14.3	1,354	60"
72"	7'-7"	4'-6"	1'-7"	3'-9"	#7	7'-5"	4'-5"	17.0	16.2	1,783	15'-1"	8'-11"	5'-7"	4'-6"	17.8	17.1	1,811	12'-5"	11'-2"	4'-3"	4'-7"	17.3	16.6	1,788	12'-5"	14'-10"	4'-3"	4'-8"	20.2	19.6	2,076	72"
84"	8'-8"	5'-0"	1'-10"	4'-3"	#8	9'-0"	5'-0"	23.7	22.8	2,595	17'-7"	10'-9"	6'-4"	5'-1"	24.8	23.9	2,596	14'-7"	13'-4"	4'-10"	5'-2"	24.1	23.3	2,511	14'-3"	17'-8"	4'-8"	5'-2"	27.9	27.0	2,990	84"